



- A Hot Water Service
- B Recirculation
- C Cold Water Feed
- D Drain Off
- E BPHE Secondary Flow
- F BPHE Secondary Return
- G Vent
- H Tapping For Stat
- A2 T&P Valve Connection

MODEL	male	male	male	male	male	male	male	female	female A2	Capacity (liters)	Weight (Kg.)
	A	B	C	D	E	F	G	H			
200	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	195	51
300	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	287	60
500	2"	1-1/2"	2"	1"	2"	2"	1"	1/2"	2-1/2"	480	91
800	2"	1-1/2"	2"	1-1/4"	2"	2"	1"	1/2"	2-1/2"	792	134
1000	2"	1-1/2"	2"	1-1/4"	2"	2"	1"	1/2"	2-1/2"	990	157

MODEL	A	B	C	D	E	F	G	H
200		1205		220		620	928	
300	Ø 620	1685	308	707	70 ±5	1107	1415	298
500	Ø 770	1690	355	616		1016	1371	345
800	Ø 950	1840		740	100	1140	1472	322
1000		2250	332	1150		1550	1882	

* Material: AISI 316
chemically descaled and passivated
* Max. working pressure: 8 bar
* Max. temperature pressure: 90° C
* Thermally insulated:
Polyurethane with C.F.C.-free

* Equipments:
- External lining
- Top cover
- Lateral hole with cover
- Control panel with thermometer